15/04/2025 16:59 pump materials

CUTES Europe Ltd

deutsch renglish español français more

contact about us

- liquid ring pumps capacity range
 - pump materials features of cutes vacuum pumps second hand vacuum pumps cone design

how it works

centrifugal fans

drain pumps

Paper Industry

Sugar industry

maintenance services

download

unit conversion



pump materials

MATERIAL CODE

Different materials of construction are available, from FCD (cast iron / nodular iron) up to SS6 (full casted 316L stainless steel) or duplex stainless steel,

but also many combinations with cast iron, stainless steel, ceramic coating, stainless steel cladding.

The material designation (for example SCS13) are based on JIS (Japanese Industrial Standards). A material equivalency chart is available in the following.

	FCD	STD	XVS	SS4	PVS	SS6	SS6L
Cones	cast iron FC-200	FC-200	SCS13	SCS13	SCS14	SCS14	CF-3M
Rotor	nodular iron (s.g.i.) FCD- 400	SCS13	SCS13	SCS13	SCS14	SCS14	CF-3M
Head	FC-200	FC-200	FC-200	SCS13	FC-200	SCS14	CF-3M
Body	FC-200	FC-200	FC-200	SCS13	FC-200	SCS14	CF-3M
cladding plates	-	-	AISI304	-	AISI316	-	-
Shaft	carbon steel S- 45C	S-45C	SUS410	SUS410	SS316	SS316	SS316L sleeves

The bearing bracket are made of cast iron. The bearing cups are made of ductile iron.

MATERIAL EQUIVALENCY CHART

	JIS (Japan)	DIN (Germany)	ASTM (USA)
Cast Iron	FC 200	GGL 200	ASTM A-48-308
Nodular Iron (s.g.i.)	FCD 400	GGG-40	ASTM 80-40
Carbon Steel	S45C	C45	AISI 1045
Stainless Steel	SCS13	1.4308 (G- X6CrNiMo 18 9)	CF - 8 (casted material, closed to AISI 304)

Conferences, exhibitions

CUTES Europe is participating to the following trade shows:

ACHEMA,

Frankfort (D) MIAC, Lucca (I)

ZELLCHEMING,

Wiesbaden (D)

15/04/2025 16:59 pump materials

Stainless Steel SCS14

1.4408 (G-X6CrNiMo18 10)

CF - 8M, (casted material, closed to AISI 316)

Stainless Steel SUS-410

1.4006 (X10Cr13) ASTM 410